




RX1260XPTR

Thermal Receipt Printer



- Easy drop-in paper loading.
- Compatible with OPOS driver





RX1260XPTR

Thermal Receipt Printer

SPECIFICATION

Printing	Printing method	Direct thermal
	Paper width	79.5±0.5mm
	Print width	Up to 72mm
	Column capacity	576 dots/line(adjustable by command)
	Printing speed	300 mm/s
	Interface	USB+Serial+Lan
	Line spacing	3.75mm (Adjustable by commands)
	Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns Chinese, traditional Chinese - 21 columns or 24 columns ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots)
	Character size	Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter	Auto cutter	Partial
Barcode Character	Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
	Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
	2D Barcode	QR CODE / PDF417
	Input buffer	2048 Kbytes
	NV Flash	256 Kbytes
Power	Power adaptor	Input: AC 220V, 50 ~ 60Hz
	Power source	Output: DC 24V/2.5A
	Cash drawer output	DC 24V/1A
Physical characteristics	Weight	1.45 Kg
	Dimensions	194.5×145×147mm (D×W×H)
Environmental Requirements	Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
	Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
Reliability	Cutter life	1.5 million cuts
	Printer head life	100Km
Software	Emulation	ESC/POS
	Driver	Windows/JPOS/Linux/Android/Mac
	Utility	Windows & Linux test Utility
	SDK	iOS, Android, Windows