



# RX1370LPTR

## Thermal Barcode Printer



### ★ APPLICATION



Shopping



Mart



Hospital



Coffe



Restaurant



Ticketing



Factory



Express

### ★ FEATURES

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 100mm label diameter, external amount and board option
- Thermal sensitive resistance, photoelectric sensor  
black mark sensor



# RX1370LPTR

## Thermal Barcode Printer



<b>Printing method</b>	Direct thermal
<b>Resolution</b>	203dpi (8dots/mm)
<b>Paper width</b>	(16 ~ 82mm)
<b>Paper roll diameter</b>	25mm ( Min ) for internal, 100mm ( Max ) for external
<b>Printing length (Max.)</b>	1000mm
<b>Paper thickness</b>	0.06 ~0.19mm
<b>Printing speed</b>	Min: 50,8mm/s Max:152mm/s
<b>Print head temperature sensor</b>	Thermal sensitive resistance
<b>Bar Codes</b>	CODE123, EAN128, ITF, CODE93, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, CODABAR, POSTNER, UPC-A, UPCA+2, UPCA+5, UPC-E, UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14
<b>Print head position sensor</b>	Micro switch
<b>Media type</b>	Label, Sticker, Continuous, gap, black mark, fan-fold, and punched hole
<b>Paper off type</b>	Tear off & peel off
<b>Internal font</b>	FONT 0 to FONT 8; Commonly used in single-byte fonts
<b>Enlargement &amp; rotation</b>	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation
<b>Gross weight</b>	1.5 kg
<b>Dimension</b>	231 (D) x 163 (W) x 150.7(H)mm
<b>Work enviroment</b>	5~45 ° C, 20~80%RH
<b>Drivers</b>	Win XP/Win 7/Win 8/Win 10/Android/IOS
<b>Input</b>	24VDC, 2,5A
<b>Paper exists detection</b>	Photoelectric sensor
<b>Interface</b>	USB+Serial / USB+Bluetooth
<b>Memory</b>	DRAM: 4M; FLASH: 4M
<b>Image</b>	Monochromatic PCX, BMP image filez can be load to FLASH, DRAM